



Remark

Electrical Specifications:

- Contact Resistance: | $30\text{ m}\Omega$ (Max)
- Insulation Impedance: $1000\text{ K}\Omega$ (Min)
- Withstanding Voltage: 500V AC 1minute

Materials:

- Rubber Core: PBT
- Terminal: Brass C2680
- Housing: Brass C2680/SPCC

Electroplating:

- Terminal: Contact area gold-plating $1\ \mu\text{m}$, Soldering area Tin flash 100-200 μm
- Housing: Whole-area copper backing 40-60 μm , Whole-area nickel plating 60-70 μm

91-US01-XXX

- 432: PBT WHITE, Copper housing
- 433: PBT Black, Copper housing

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ±0.10
.XX ±0.25
.X ±0.35
.X' ±3'

PART NAME:	USB AF 10.0 180 Crimping	
------------	--------------------------	--

PART NO:	See Table	C
----------	-----------	---

SHENZHEN KINGHELM ELECTRONIC CO., LTD.	WWW.BDS666.COM
--	----------------

KH-AF180ZJ-10-JB	0755-83044319
------------------	---------------

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED
					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT:	SCALE REV(NO) SHEET	DRAWN
					mm	1:1 A 1 OF 1	DATE

Hexing
2011.12.05