



截面 A-A

Remark

Electrical Specifications:

Contact Resistance: $30\text{ m}\Omega$ (Max)

Insulation Impedance: $1000\text{ K}\Omega$ (Min)

Withstanding Voltage: 500V AC 1minute

Materials:

Rubber Core:

PBT

Terminal:

Brass C2680

Housing:

Brass C2680/SPCC

Electroplating:

Terminal:

Contact area gold-plating $1\text{ }\mu\text{m}$,
Soldering area Tin flash $100\text{-}200\text{ }\mu\text{m}$

Housing:

Whole-area copper backing $40\text{-}60\text{ }\mu\text{m}$,
Whole-area nickel plating $60\text{-}70\text{ }\mu\text{m}$

91-US01-XXX

- 650: PBT WHITE, Copper housing
- 651: PBT Black, Copper housing

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ±0.15
.XX ±0.30
.X ±0.45
.X' ±3'

PART NAME:	USB AF 10.0 180 without crimping
PART NO:	See Table
SHENZHEN KINGHELM ELECTRONIC CO., LTD.	
WWW.BDS666.COM	
PART NO:	KH-AF180ZJ-10
DATE:	0755-83044319

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED
					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT:	SCALE	REV(NO)
					mm	1:1	A
						SHEET	DRAWN
						1 OF 1	DATE
							2011.12.05