



P.C.B Reference drawing

Thickness of 1.6mm is recommended

Parameters:

1. Rated Voltage, Current: 125V/1.5A max
2. Contact Resistance: 40m Max
3. Insulation Resistance: 500M Min
4. Test Conditions: AC1000V/0.5mA for 1 minute
5. Salt spray test: 8±0.5H
6. Soldering Temp: 260±5 3±0.5s

Other Requirements

1. There shall be free from wrong packing, missing parts, etc;
2. The surface of parts shall be free of cracks, lack of materials, flash etc, and the coating on the surface shall be bright and artistic
3. The unspecified dimensional tolerance shall be calculated as ±0.15mm

Material requirements

1. Base: PA66 Black
2. Shielded: H62 Copper
3. Signal pin: Phosphor copper, gold plating
4. LED pin: Iron pin

Issuing department	
Administration Department	
Business department	
Purchasing Department	
Engineering department	
QC Department	
Production department	

							View		SHENZHEN KINGHELM ELECTRONIC CO., LTD.	
									WWW.BDS666.COM	
Mark	Number of Revised		Revised Document Number		Signature	Date	Drawing Mark	Weight	Scale	0755-83044319
Designed	LI PANJIN	Date	13.09.24	Standardization		Date				KH-5224-8P8C-D
Proofread		Date		Examined and approved		Date				
Craft		Date								Network socket
Checked	WANG XIAOFENG	Date	13.09.24				Page in Total	Page in Total		