



Main parameters:

1. Rated Voltage:, Rated Current: 125V/1.5A max
2. Contact Resistance: 40mΩ Max
3. Insulation Resistance: 500MQMin
4. Dielectric Withstand Voltage Test: AC1000V/5.0mA for 1 minute
5. salt spray test: 8±0.5H
6. Welding temperature: 260±5 3±0.5s

Other requirements :

1. Products should be free from wrong installation, missing parts etc
2. The surface of parts should be free of cracks, lack of materials, flash etc, and the surface coating should be bright and beautiful
3. The dimension tolerance without injection is ±0.15 mm for soil

		Phosphor Bronze		
4	Signal pin		Gold -Pating	
3	Rear Cover	PA66	Black(Environmental-Frienv,Flv)	
2	plastic Base	PA66	Black(Environmental-Frienv,Flv)	
1	Shielded	Brass	Copper Tin-plating	
No.	Designation	Materials	Electroplating	Remark

- Issuing department
- Administration Department
- Business department
- Purchasing Department
- Engineering department
- QC Department
- Production department
- examined and approved

Unspecified Tolerance			
Rank	A	B	C
0~4	0.05	0.10	0.20
4~16	0.08	0.15	0.30
16~64	0.12	0.25	0.50
64~250	0.25	0.40	0.80

						View		SHENZHEN KINGHELM ELECTRONIC CO., LTD.	
								WWW.BDS666.COM	
Mark	Number of Revised	Revised Document Number	Signature	Date	Drawing Mark	Weight	scale	0755-83044319	
Designed	Li Panjin	Date 13. 04. 22	Standardizati on	Date				KH-RJ45-58-8P8C	
Proofreadin		Date	Checked	Date				network socket	
Craft		Date							
Checked	Wang Xiaofeng	Date 13. 04. 22						1 Page in Total	Page 1