



PCB LAYOUT

Model: KH-A2001WF-(02-20)A

SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon 6T, UL94V-0
PIN Brass Tin-plated
Solder tad Brass Tin-plated

NO.	mm		
	A	B	C
A2001WF-02A	2.00	8.00	6.70
A2001WF-03A	4.00	10.00	8.70
A2001WF-04A	6.00	12.00	10.70
A2001WF-05A	8.00	14.00	12.70
A2001WF-06A	10.00	16.00	14.70
A2001WF-07A	12.00	18.00	16.70
A2001WF-08A	14.00	20.00	18.70
A2001WF-09A	16.00	22.00	20.70
A2001WF-10A	18.00	24.00	22.70
A2001WF-11A	20.00	26.00	24.70
A2001WF-12A	22.00	28.00	26.70
A2001WF-16A	30.00	36.00	34.70

DRAWN	DESCRIPTION	DATE	GENERAL TOLERANCE		DRAWING	HE JUNJU	PART NO.	REV.	A
			$X. \pm 0.25$	$X.^{\circ} \pm 2^{\circ}$	CHECK	2013. 07. 01			
			$.X \pm 0.20$	$.X^{\circ} \pm 1^{\circ}$	APPROVAL	LAI JIREN	TITLE	PH SMT	SHEET 1/1
			$.XX \pm 0.15$	$.XX^{\circ} \pm 0.5^{\circ}$		2013. 07. 03	CUTM. NO.	WAFF SMT TYPE	
			$.XXX \pm 0.10$	$.XXX^{\circ} \pm 0.5^{\circ}$	UNITS	ZHANG SONGQIANG			
						2013. 07. 05			
					MM		SHENZHEN KINGHELM ELECTRONIC CO., LTD.	WWW.BDS666.COM	
					SCALE		KH-A2001WF-02A	0755-83044319	
					1:1				