

# SHENZHEN KINGHELM ELECTRONIC CO., LTD.

### KH-MMCX-K510-Z

## High frequency connector specification

- (Product Code): XK2013 mmcx-j-1.3
- (Product Name): High frequency socket
- (Part Number): KH-MMCX-K510-Z
- (Environment protect information): Meet RoHS requirements
- (Safety information): None
- (Interface standard): Next page
- (Technical parameter)
  - **■** (Electrical performance)
    - $\triangle$  (Characteristic impedance):  $50\Omega$
    - $\triangle$  (Rated current):  $0^{\sim}18\text{GHz}$
    - ▲ (Contact resistance) : Inner conductor ≤ 3mΩ Outside conductor ≤ 2mΩ
    - ▲ (Dielectrically withstanding voltage): 1000VRMS
    - ▲ (Voltage rating): 335 VRMS
    - **△** (Insulation Resistance):  $\geq 5000 \text{M} \Omega$

### **■** (Mechanical performance)

- ▲ (Inner conductor separating force): ≥0.28N
- ▲ (Durability): 500 times

#### **■** (Material and surface treatment)

- ▲ (Metal material, workmanship and surface treatment)
- ♦ (Contact)

```
\begin{tabular}{ll} \beg
```

(Workmanship): Machining

♦ (Shell)

(Material): Copper-Gold pating (Surface Treatment): Nickel-Gold Plating

(Workmanship): Machining

- ▲ (Plastic, Workmanship And Forming)
- ♦ (Insulator)

(Material): PTFE

(Workmanship): Machining

- (Operation environment)
  - ▲ (Temperature Range): -55°C $\sim+155$ °C
  - $\blacktriangle$  (Shock): 500 m/s<sup>2</sup>
  - $\blacktriangle$  (Vibration):  $10\sim2000\text{Hz}$ ,  $10\text{m/s}^2$
- (Structure And Dimension)
  - (Maximum dimension of plug):
- (Brief Introduction):
  - (Package and Store) 100PCE/pag





