

CUSTOMER :		Customer Part NO.			
		Part Descripon			
Item	Specification				
NO. of conductors	N 6P-96P				
Pitch	P 0.5 ± 0.05				
Total Pitch	PT 2.5-47.5 ± 0.08				
Total Length	L 25-20000 ± 2				
Insulation Length	IL 25-20000 ± 2				
Margin Width	M 0.5 ± 0.08				
Total Width	W 3.5-48.5 ± 0.08				
Strip Length	S1 1.5-5 ± 0.5				
Strip Length	S2 1.5-5 ± 0.5				
Reinforeing tape length	B1 2.5-30 ± 2				
Reinforeing tape length	B2 2.5-30 ± 2				
Slanting	A ≤ 0.3				
Over lap	/				
Terminal thickness	t1 0.3 ± 0.02				
Thickness insulation	t 0.12 ± 0.02				
Conductor thickness	Ct 0.035 ± 0.01				
Conductor width	Cw 0.3 ± 0.03				
Supporting Tapc Color	Blue	Temp:15° C~25° C		Humidity:30~60RH%	
PET(Supporting Tapc Color)	0.225mm	Drawing Not TO Scale Hidden Lines Not Shown	Discharge Date	Review Date	Drawing NO
PET(Insulation)	0.043mm Printing		2021-05-19		
PET(Insulation)	0.043mm White		SHENZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDS666.COM
Rev	B		KH-FFC-V0.5-18P-100MM		0755-83044319