

CUSTOMER :		Customer Part NO.						
		Part Descripon						
Item	Specification							
NO. of conductors	N 4P-96P							
Pitch	P 1.0 ± 0.08							
Total Pitch	PT 3-95 ± 0.1							
Total Length	L 25-20000 ± 2							
Insulation Length	IL 25-20000 ± 2							
Margin Width	M 1.0 ± 0.1							
Total Width	W 5-97 ± 0.1							
Strip Length	S1 1.5-5 ± 0.5							
Strip Length	S2 1.5-5 ± 0.5							
Reinforeing tape length	B1 2.5-30 ± 2							
Reinforeing tape length	B2 2.5-30 ± 2							
Slanting	A ≤ 0.3							
Over lap	/							
Terminal thickness	t1 0.3 ± 0.02							
Thickness insulation	t 0.12 ± 0.02							
Conductor thickness	Ct 0.035 ± 0.01							
Conductor width	Cw 0.65 ± 0.03					Storage condition :Recommended		
Supporting Tapc Color	Blue					Temp:15° C~25° C Humidity:30~60RH%		
PET(Supporting Tapc Color)	0.225mm					Drawing Not TO Scale Hidden Lines Not Shown	Discharge Date	Review Date
PET(Insulation)	0.043mm Printing	<p>Unit:mm</p>	2021-05-19					
PET(Insulation)	0.043mm White		SHENZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDS666.COM			
Rev	B		KH-FFC-V1.0-8P-100MM		0755-83044319			