

CUSTOMER :		Customer Part NO.				
		Part Descripon				
Item	Specification					
NO. of conductors	N					6P-96P
Pitch	P					0.5±0.05
Total Pitch	PT					2.5-47.5±0.08
Total Length	L					25-20000±2
Insulation Length	IL					25-20000±2
Margin Width	M					0.5±0.08
Total Width	W					3.5-48.5±0.08
Strip Length	S1					1.5-5±0.5
Strip Length	S2					1.5-5±0.5
Reinforeing tape length	B1					2.5-30±2
Reinforeing tape length	B2					2.5-30±2
Slanting	A					≤0.3
Over lap						/
Terminal thickness	t1					0.3±0.02
Thickness insulation	t					0.12±0.02
Conductor thickness	Ct					0.035±0.01
Conductor width	Cw					0.3±0.03
Supporting Tapc Color	Blue	Temp:15° C~25° C	Humidity:30~60RH%			
PET(Supporting Tapc Color):	0.225mm	Drawing Not TO Scale Hidden Lines Not Shown	Discharge Date	Review Date	Drawing NO	
PET(Insulation)	0.043mm		2021-05-19			
PET(Insulation)	0.043mm		SHENZHEN KINGHELM ELECTRONIC CO., LTD		WWW. BDS666. COM	
Rev	A	Unit(单位):mm	KH-FFC-A0.5-20P-200MM		0755-83044319	