


Technical Specifications	Specification
Operation Condition:	- 40 ~ 55°C
Rating:	DC 30V 0 SA
Contact Resistance:	≤ 0.03
Insulation Resistance:	≥ 100MΩ DC250V
Withstand Voltage:	AC 500V (50Hz)/min
Insertion-withdrawal Force:	3~20N
Mechanical Life:	5000 times

Schematic of PCB



Serial No.	Part Number or Code	Quantity	IPCS	Materials	Remark
4			Grounding Piece	IPCS	Brass t=0.25 Electroplating: Silver
3			Reed	IPCS	Brass t=0.26 Electroplating: Silver
2			Contact Pin	IPCS	H62Brass Strip t = 0.20 Electroplating: Silver
1			Base	IPCS	PA66(Black)

TOLERANCE: UNLESS OTHERWISE SPECIFIED
UNOER 1.5±0.05 | 1.5~10±0.1 | OVER 10±0.2

					SHEN ZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDS666.COM			
					KH-DC-031A-1.3STM		0755-83044319			
Mark	Number of Revised	Revised Document Number	Signature	Date	DC-0131A		Drawing Mark	Weight	Scale	
Drawn							A B	1:1		
Designed							1 Page in Total		Page 1	
Checked										
Craft										
Standardized					Electrical Socket					
Approved										