



Height : 4.3 4.5 5 6.....21

ITEM	Technical Specifications
Press force	A: 130±30 gf B:160±30 gf C:250±30 gf
Stroke	0.25±0.1 mm
Life	Electrical Life≥100,000 times
Exterior	No important injection molded defects and waste products
Withstand Voltage	250V / 1min、No flashover
Handle	The motion is flexible without jamming, and the press forces felt under the same specification and category are relatively consistent
Circuit Transformation	The electrical inspection ($\leq 8V, 0.15A$) shows that the circuit is under normal condition.
solderability	The tin bonding area is greater than 95% of the immersion area.
Protection level	—
Resistance to solder	260±5°C/5s, functional motion, circuit transformation and appearance are in good condition.
Insulation resistance	$\leq 30m\Omega$
Insulation resistance	$\geq 100M\Omega$
ROHS compliance	Execution compliant to customer's requirements
Proprietary technology	—

5	Terminal (Pins)	Brass	1	2500-01.001
4	Base SW-60	PA plastic	1	2500-01.002
3	5 Flexible Pieces	Phosphate/stainless steel	1	2500-01.003
2	Holder SW-6	Cold -rolled steel	1	2500-01.004
1	Lever SW-60	PA plastic	1	2500-01.005
NO.	Product name	Materials	Quantity	Drawing No.

SHENZHEN KINGHELM ELECTRONIC CO., LTD.		WWW.BDSS666.COM		HE JUNJU		LAI JIREN		Product Image		
KH-6X6X11H-ZJ		0755-83044319		Designed		Mould		Quality control		
O/A		Issue		Revised Order No.		Approval		X		
Version No.		Revision history		4		7		XX ±0.1 Project name Tact Switch		
1		2		3		5		Angle ±0.5° Part No.		
2		4		6		8		Page 1 OF 1 Unit:mm Scale:1:1 Paper A4		
3		5		7		9		10		
4		6		8		10		11		