


REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



三個配件出貨時另外附配件出貨(墊片,華司,螺母)

**NOTES:**

1. ELECTRICAL:
  - 1.1. VOLTAGE RATING:DCV 300V 10MS
  - 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
  - 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
  - 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
  - 1.5. IT SHOULD BE NO ANY OPENS/SHORT, MISWIRING AND INTERMITTENT FAILURES.
2. MATERIAL:
  - 2.1. SEE TABLE
3. ALL COMPONENTS ARE ROHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
③	套管	黑色热缩套管, OD:2.0MM	AS
②	接头	SMA母头母针, 分体, 11牙, 镀金	1
①	同轴线	RF 1.37黑色线, OD: 1.37mm	AS

深圳市金航标电子有限公司 [www.bds666.com](http://www.bds666.com)

型号: KH-122-137SMA-200 0755-83044319

ALL DIMENSION ARE IN MM		DRAWN	DATE	SMA / F TO OPEN L=200mm	
COMPUTER GENERATED IN SOLIDWORKS		Jamy	2020-06-15	SIZE	REV
DO NOT SCALE THIS DRAWING		ENG.		B	A
PROJECTION		MFG.		SCALE: Free	TYPE
GENERAL TOLERANCE FOR ANGLES X.X ± 1° X.XX ± 0.3 X.XXX ± 0.25 X.XXX ± 0.150		Q.A.			SHEET 1 OF 1

CUSTOMER P/N:

4

3

2

1

D

C

B

A

4

3

2

1

D

C

B

A