



NOTE:

1 MATERIAL:

- a. HOUSING: PBT BLACK; RoHS
- b. CONTACT: C2680 BRASS; FINISH: TIN PLATED

2 ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTIC VOLTAGE: 500V AC ONR SES LEVEL
- d. OPERATING TRMPERATURE: -55° C TO 105° C

△4	增加正、负极高度尺寸	2020.05.25	Peng	深圳市金航标电子有限公司		www.kinghelm.com.cn							
△3	变更正极固定柱宽度	2018.06.02	Peng	KH-CR2032-2-1		0755-28190160							
△2	增加PCB Layout "+" "-" 标识	2018.03.24	Peng	一般公差(TOLERANCES) DECIMALS: X :±0.3 X.X :±0.2 X.XX :±0.1 X.XXX :±0.05 ANGLES: X :±1° X.X :±0.5°	品名 (TITLE)	BATTERY HOLDER CR2032-2-1 环保 镀锡	制图 (DR)	Joseon_he 2015.07.13					
△1	整体修正	2017.09.06	Peng		料号 (PART NO)	KY-10001-1-1 301E01001	核准 (APPD)	Jack_mei 2015.07.13					
序号	变更内容	变更日期	变更人	比例(SCALE)	1:1	单位(UNITS)	mm	REV	F	SIZE	A4	张数(SHEET)	1 OF 1