



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

| 编 号       | 尺寸 (mm) |       |
|-----------|---------|-------|
|           | A       | B     |
| A2026-02Y | 2.00    | 6.00  |
| A2026-03Y | 4.00    | 8.00  |
| A2026-04Y | 6.00    | 10.00 |
| A2026-05Y | 8.00    | 12.00 |
| A2026-06Y | 10.00   | 14.00 |
| A2026-07Y | 12.00   | 16.00 |
| A2026-08Y | 14.00   | 18.00 |
| A2026-09Y | 16.00   | 20.00 |
| A2026-10Y | 18.00   | 22.00 |
| A2026-11Y | 20.00   | 24.00 |
| A2026-12Y | 22.00   | 26.00 |
| A2026-16Y | 30.00   | 34.00 |

| 制图<br>DRAWN | 变更内容<br>DESCRIPTION | 日期<br>DATE | GENEAL TOLERANCE |            | 制图<br>DRAWING  | 钱岳生<br>2014、10、20 |             | 料号<br>PART NO.    | A2026-nY     |  | 版本<br>REV.          | A   |
|-------------|---------------------|------------|------------------|------------|----------------|-------------------|-------------|-------------------|--------------|--|---------------------|-----|
|             |                     |            | X.±0.25          | X.*±2'     | 审核<br>CHECK    | 张名<br>2014、10、21  |             | 品名<br>TITLE       | PA孔座         |  | 页次<br>SHEET         | 1/1 |
|             |                     |            | .XX±0.20         | .X'±1'     | 核准<br>APPROVAL | 张名<br>2014、10、23  |             | 客户料号<br>CUTM. NO. | 深圳市金航标电子有限公司 |  | www.kinghelm.com.cn |     |
|             |                     |            | .XX±0.15         | .XX'±0.5'  | 单位<br>UNITS    | MM                | 比例<br>SCALE | 1:1               | KH-A2026-11Y |  | 0755-28190160       |     |
|             |                     |            | .XXX±0.10        | .XXX'±0.5' |                |                   |             |                   |              |  |                     |     |