



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance:  $20\text{m}\Omega$  Max
- 5、Insulation Resistance:  $1000\text{M}\Omega$  Min
- 6、Withstanding Voltang:  $1000\text{V AC/minute}$
- 7、Material: Wafer LCP, UL94V-0  
PIN Brass Tin-plated  
Solder tad Brass Tin-plated

| 编号          | 尺寸 (mm) |       |       |
|-------------|---------|-------|-------|
|             | A       | B     | C     |
| A2504-02AWB | 2.50    | 7.50  | 10.00 |
| A2504-03AWB | 5.00    | 10.00 | 12.50 |
| A2504-04AWB | 7.50    | 12.50 | 15.00 |
| A2504-05AWB | 10.00   | 15.00 | 17.50 |
| A2504-06AWB | 12.50   | 17.50 | 20.00 |
| A2504-07AWB | 15.00   | 20.00 | 22.50 |
| A2504-08AWB | 17.50   | 22.50 | 25.00 |
| A2504-09AWB | 20.00   | 25.00 | 27.50 |
| A2504-10AWB | 22.50   | 27.50 | 30.00 |
| A2504-11AWB | 25.00   | 30.00 | 32.50 |
| A2504-12AWB | 27.50   | 32.50 | 35.00 |

| 制图<br>DRAWN | 变更内容<br>DESCRIPTION | 日期<br>DATE | GENERAL TOLERANCE |                 | 制图<br>DRAWING  | 钱岳生<br>2013、07、01 |             | 料号<br>PART NO.    | A2504-nAWB             |  | 版本<br>REV.          | A   |
|-------------|---------------------|------------|-------------------|-----------------|----------------|-------------------|-------------|-------------------|------------------------|--|---------------------|-----|
|             |                     |            | $X \pm 0.25$      | $X \pm 2'$      | 审核<br>CHECK    | 张名<br>2013、07、03  |             | 品名<br>TITLE       | HA卧贴<br>WAFER SMT TYPE |  | 页次<br>SHEET         | 1/1 |
|             |                     |            | $.X \pm 0.20$     | $.X \pm 1'$     | 核准<br>APPROVAL | 张名<br>2013、07、05  |             | 客户料号<br>CUTM. NO. |                        |  |                     |     |
|             |                     |            | $.XX \pm 0.15$    | $.XX \pm 0.5'$  | 单位<br>UNITS    | MM                | 比例<br>SCALE | 1:1               | 深圳市金航标电子有限公司           |  | www.kinghelm.com.cn |     |
|             |                     |            | $.XXX \pm 0.10$   | $.XXX \pm 0.5'$ |                |                   |             |                   | KH-A2504-10AWB         |  | 0755-28190160       |     |