



1. Material and Plating:

Pin Cylinder: Brass alloy, nickel-plated 50-60 μ ", gold-plated 1 μ ".

Pin Head: Brass alloy, nickel-plated 50-60 μ ", gold-plated 1 μ ".

2. Operating Current: 1.0A

3. Operating Voltage: Below 12V @ 25°C

4. Salt Spray Test: No corrosion after 24 hours in 5% salt solution.

5. Solderability Test: Wetting solder at 230 \pm 5°C for 1 second, with solder coverage rate above 95%.

Shenzhen Kinghelm Electronics Co., Ltd				www.kinghelm.net			
KH-PG2012005-DZ				0755-83044319			
	Third Angle Projection	Item Name	pogopin	Date	2018/10/22		
Tolerances Not Specified Refer to Standards		0.02	Specification	PG2.0-12.0-0.5T	Design	Mr. He	
0 = \pm 0.1		ϕ 0.03	Material	Copper Rod C3604	Review	Mr. Lai	
0.0 = \pm 0.05		0.02	Customer Part Number		Recognise	Mr. Zhang	
0.00 = \pm 0.02		0.04	Surface Treatment	Gold-plated	Unit	mm	
0.000 = -		0.02	Drawing Number	XYX-00031	Scale	1:1	
Do Not Measure According to Drawings			Version	1	REV: A		

Date	Revision Contents	Version	Notes
		5	
		4	
		3	