



Straight Edge

Characteristics:

1. Rated Current: 1.5 AMP at 250V AC
Rated Voltage: 30V
2. Insulation Resistance: Minimum 1000M
3. Contact Resistance: Maximum 30m
4. Withstanding Voltage Strength: 500V AC
5. Temperature Range: -20 ~ 60°C
6. Insertion Force $\leq 35\text{N}$
7. Extraction Force $\geq 10\text{N}$

Remarks:

1. There must not be loose, deformation phenomenon.
2. Pin must not be bent or deformed.
3. Environmental requirements: EU environmental protection
4. With "▲" for the first piece of inspection size
5. With "▲" for the first piece and process inspection size

RECOMMENDED P.C.B PATTBRN LAY OUT

Manufacture DWG		Shenzhen Kinghelm Electronics Co., Ltd					www.kinghelm.net				
Tolerance Unless Otherwise		KH-2AF90CB-17					0755-83044319				
.X±0.15	.X.±5'	Date	DATE	Unit	MM	Drawing	Drawing	DWG No.	DWGNO.		
XX±0.05	.X.±2'	Checked	Checked	Scale	1 : 1	Design	Design	Name	Double layer sinker 10.5 straight edge		
XXX±0.02	.XX±1'	Approved	Approved	View				Ver	VER	Sheet	PG1