



Rev	ECN Number	Description	Date	Drawn	Checked	Approved

### Technical Requirement

1. Material: Stainless steel SUS304, T=0.10 ±0.005.
2. The soldering and contact surfaces of the terminal must be free from burrs, maximum burr size of 0.03mm allowed on other parts.
3. Torsion: 45° per 1000mm, Arch: 5mm per 1000mm.
4. Dimensions marked with ' ' are critical for control and inspection.
5. Unmarked R MAX R0.13.
6. The plating must pass a 48-hour salt spray test.
7. Life test > 20, 000 cycles, product spring force requirement between 60gf to 80gf.
8. Nickel base 50-80µm minimum, gold-plated in the welding area, gold-plated 1µm minimum in the contact area.



Shenzhen Kinghelm Electronics Co.,Ltd www.kinghelm.net Model: KH-351538-TP 0755-83044319	General Tolerance		Scale: 1:1	Drawn	Date	DWG. No. 681-0019B-1	Diagram for Customer RF Antenna Spring, SMT, L3.5*W1.5*H1.8 mm	REV.
	XX. ± 0.50	X.° ± 2.0°						A
	X. ± 0.35	.X° ± 1.0°	Sheet					
	.X ± 0.25	.XX° ± 0.5°	1/1					
0755-83044319	.XX ± 0.15	.XX° ± 0.5°	Size: A4	Approved	Date	FDX0019B1		