


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
③	套管	黑色热缩套管, OD:3.5*15MM	2
②	接头	FAKRA接头母头母针,蓝色外壳, C型	2
①	同轴线	174同轴线 黑色外被,OD:2.8mm	AS

深圳市金航标电子有限公司

SHENZHEN KINGHELM ELECTRON CO.,LTD.

WWW.KINGHELM.COM.CN

0755-28190160

ALL DIMENSION ARE IN MM	DRAWN	Jamy	DATE	2024-06-17
	ENG.	ALAN		2024-06-17
COMPUTER GENERATED IN SOLIDWORKS	MFG.	KEN		2024-06-17
	Q.A.	TONY		2024-06-17

KH-FAKRACK-FAKRACK-RG174-300M

DO NOT SCALE THIS DRAWING	PROJECTION	GENERAL TOLERANCE FOR ANGLES	X.X	X.XX
		±	1° ±	0± 0.25 0.150

SIZE	Number	REV
B	X.XXX	A

SCALE: Free TYPE SHEET 1 OF 1

NOTES:

1. ELECTRICAL:
 - 1.1. VOLTAGE RATING:DCV 300V 10MS
 - 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
 - 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
 - 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
 - 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.
2. MATERIAL:
 - 2.1. SEE TABLE
3. ALL COMPONENTS ARE RoHS COMPLIANT.

CUSTOMER P/N: