


Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
③	套管	黑色热缩套管, OD:3.5*15MM	2
②	接头	FAKRA接头母头母针,蓝色外壳, C型	2
①	同轴线	174同轴线 黑色外被,OD:2.8mm	AS

深圳市金航标电子有限公司

SHENZHEN KINGHELM ELECTRON CO.,LTD.

WWW.KINGHELM.COM.CN

0755-28190160

ALL DIMENSION
ARE IN MM

DRAWN Jamy DATE
2024-06-17

ENG. ALAN 2024-06-17

COMPUTER GENERATED
IN SOLIDWORKS

MFG. KEN 2024-06-17

DO NOT SCALE
THIS DRAWING


Q.A. TONY 2024-06-17

SIZE Number

B X.XXX

REV

A



GENERAL TOLERANCE FOR
ANGLES X.X X.XX
± 1° ± 0.3 0.25 0.150

SCALE: Free TYPE

SHEET 1 OF 1

NOTES:

1. ELECTRICAL:

- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

- 2.1. SEE TABLE

3. ALL COMPONENTS ARE RoHS COMPLIANT.

CUSTOMER P/N: